



地址：浙江省宁波市会展路 181 号 Add: No.181,HuiZhan Road ,Ningbo city, China 315000
电话：(Tel)86-574-87990349， 传真 (Fax) :86-574-88193499 邮编 (P.C) :315000
<http://www.tcipacking.com> <http://www.rubbersealing.com> E-mail: sales@tcipacking.com

PTFE tubing



PTFE tubing

We use PTFE granular resin by ram extrusion method to make the PTFE tubings. PTFE is a kind of famous plastic with its best chemical resistance, and PTFE tubing also has the best electrical properties among of the plastics.

SPECIFICATION OF T.C.I PTFE TUBING:

Specifications	outside diameter (mm)		wall thickness (mm)		Length (mm) min
	Nominal	Tolerance	Nominal	Tolerance	
24x2 25x2 29x2 29.6x2	24 25 29 29.6	±0.65	2	±0.30	4000
32x2 32x3.5 40x2 40x4 50x4 50x5	32 32 40 40 50 50				
		2	±0.30		
		4	±0.38		
			5		
51x2 52x4 64x2.5 64x4.5 81x2.5 82x2.5 82x3	51 52 64 64 81 82 82	±0.95	2	±0.30	
			4	±0.38	
			2.5		
		4.5			
			2.5		
			3		
90x3 90x5 104x3	90 90 104	±1.10	3	±0.30	
			5		
			3		
129x3.5 154x4 204x4	129 154 204	±1.20	3.5	±0.35	
			4		
			4		

[Main properties]

Properties	unit	Result
Apparent density	g/cm ³	2.10-2.30
Tensile strength(min)	MPa	18
Ultimate elongation(min)	%	230